

# D140



Power over  
Ethernet (PoE)



IPv6 & IPv4



Headset  
connectable



Security (TLS  
& SRTP)



SmartLabel



HD audio



OpenVPN

## D140 - the ideal entry-level device for your everyday office life

The D140 is suitable for all work environments in which cost-effective but high-quality communication is required. The device, equipped with a slate gray

Two freely programmable SmartLabel keys, six

dedicated and four context-sensitive function keys are available for simple and intuitive operation. The D140 is ideal for large installations, e.g. in public administrations.

## Basics

- Product information
  - IP desk phone
  - PN 00004651
  - Colour: slate gray
  - Operating system: Linux
- Placement: indoor, desktop, wall mounting<sup>1</sup>

## Dimensions and weight

- Dimensions (L x W x H, approx.) without footstand
  - 205 mm x 185 mm x 40 mm
- Dimensions (H x W x D, approx.) with footstand
  - 205 mm x 185 mm x 220 mm (high angle 46°)
  - 205 mm x 185 mm x 200 mm (low angle 28°)
- Weight (approx.):
  - 710 g without footstand
  - 830 g with footstand

## Display and indicators

- Display
  - TFT liquid crystal display (LCD), graphical, grayscale, backlit
  - Size (diagonal): 2.8" (67 mm)
  - Size (W x H): 59 mm x 33 mm
  - Resolution: 320 x 240 pixel
- 5 LED indicators
  - Call status indication: 1 red LED
  - Function key status indication: 4 multicolour LEDs

## Keypad and function keys

- 36 hard keys in total
- 12 keys (standard ITU telephone keypad)
- 4 context-sensitive function keys
- 5-way navigation key
- 2 SmartLabel keys (with multicolour LED)
- 5 dedicated audio keys
  - Mute, Speakerphone, Headset, Volume + / - (rocker)

- 6 dedicated function keys
  - Ok, Cancel, DND, Message (with red LED), Directory, Menu, Transfer, Hold
- Keyboard lock

## Audio devices, codecs and features

- Corded receiver:
  - Hearing aid compatible (HAC)
- Audio codecs
  - G.711 (A-law,  $\mu$ -law), G.722, G.726, G.729, GSM 6.10 (FR)
- Dual-tone multi-frequency signalling (DTMF / RFC2833)
  - SIP-INFO, in-band, out-of-band
- Related features
  - Built-in assignable ringtones
  - Comfort Noise Generator (CNG)
  - Voice Activity Detection (VAD)

## Interfaces and connections

- D140 power options
  - Power over Ethernet (PoE)
    - IEEE 802.3af, class 1 | IEEE 802.3az<sup>3</sup>
  - Power adapter<sup>1</sup>
    - 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W
- Wired interfaces
  - Power adapter:<sup>1</sup> coaxial power connector (socket)
  - Ethernet 10/100 Mbit/s: 2 x RJ45-8P8C sockets
  - Corded receiver: RJ9-4P4C socket
  - Headset:<sup>1</sup> RJ9-4P4C socket
  - EHS adapter:<sup>1</sup> RJ12-6P6C (EHS) socket
- Sensors
  - Hook switch sensor

## User interfaces and setup

- Configuration and setup via menu-driven web user interface (WUI)
  - Password-protected login
  - Secure web server/client (HTTPS)
- Configuration and setup via menu-driven phone user interface (PUI)
- Customisation: XML browser
- Automatic configuration via provisioning
  - Loading of settings and firmware via HTTP / HTTPS / TFTP
  - Supported DHCP provisioning options 66 / 67
  - Secure Redirection And Provisioning Service (SRAPS) support
  - Plug & Play (PnP) support
  - Remote management via TR-069 / TR-069 Annex G (TR-111)
- Localization
  - Languages
  - Timezone, dial tone
- Diagnostic: SIP trace, PCAP trace, Syslog

## Networking technologies and protocols

- Network technologies
  - OpenVPN, VLAN (IEEE 802.1Q)
- VoIP related protocols and techniques
  - SIP (RFC 3261), SDP (RFC 3261), RTP (RFC 8866), RTCP (RFC 3550), RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), ENUM, ICE, STUN (RFC 5389)
- Secure VoIP protocols
  - SIPS (SIP over TLS), SRTP (RFC 3711), SRTCP
- Network protocols
  - IPv4 / IPv6 (dual stack), DHCP, NTP, LDAP, LLDP-MED, HTTP, TFTP, L2TP
- Secure network protocols
  - TLS V1.2, HTTPS, IEEE 802.1X (EAPoL)
- Remote management protocols
  - TR-069, TR-069 Annex G (formerly TR-111)

## Directory support and call features

- 2 SIP identities / accounts
  - Up to 2 simultaneous calls
- Directory support
  - LDAP (server-based directory)
  - Local directory with up to 1,000 entries
- Outgoing call features
  - Speed dialling via function keys
  - URL dialling
  - Local dial plan
  - Redial (via dialed calls list)
  - Automatic redial on busy
  - Caller identification (CLIP)
  - Calling Line Identification Restriction (CLIR)
  - Call completion (busy/unreachable)<sup>2</sup>
  - Intercom
  - Multicast paging
- Incoming call features
  - Call waiting/swapping
  - Call barring/blocking: deny list, anonymous calls, Do Not Disturb (DND) mode
  - Auto answer
  - Call diversion
- Connected call features
  - Mute microphone
  - Hold
  - Music on hold<sup>2</sup>
  - Blind call transfer
  - Attended call transfer
  - 3-way local conferencing
  - Call park / unpark<sup>2</sup>
  - Client Matter Code (CMC)<sup>2</sup>
- Related features
  - Call history lists of missed, received, dialed, rejected, and deflected calls
  - Extension monitoring (Busy lamp field), call pickup<sup>2</sup>

## Interoperability

- Certified VoIP partner

## Environmental conditions

- Operating ambient temperature: 0 °C - 35 °C
- Nonoperating (storage) temperature -10 °C - 45 °C
- Humidity (non-condensing): 5 % - 95 %

## Package contents

- Hardware
  - IP desk phone D140
  - Footstand
  - Corded receiver
  - Ethernet cable

- Documentation
  - Quick Installation Guide (QIG)
  - GNU General Public License

## Snom accessories and compatible devices

- Power adapter
  - [Snom 10 W PSU \(PN 00004570\)](#)
- EHS adapter
  - [EHS Advanced 2.0 \(PN 00004343\)](#)
- Wired headset via RJ9-4P4C
  - Monaural: [A100M \(PN 00004341\)](#)
  - Binaural: [A100D \(PN 00004342\)](#)
- DECT headset via RJ9-4P4C
  - [A170 \(PN 00004387\)](#)
- Third party headset support
  - [Please check compatibility list](#)



10 W PSU



EHS 2.0



A100D



A100M



A170

<sup>1</sup> Available separately

<sup>2</sup> If supported by PBX

<sup>3</sup> Optional via software

## Series overview



D120



D140



D150

## Disclaimer

Further information : [Snom website](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#)

Snom is a registered trademark of Snom Technology GmbH in the European Union, USA, Japan, China and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, are legally protected trademarks of Snom Technology GmbH. Other mentioned trademarks or registered trademarks are the property of their respective manufacturers or owners. Product specifications are subject to change without notice. We do not accept liability for printing errors and mistakes.