

# D765



USB port



Power over Ethernet



IPv6 & IPv4



Gigabit Ethernet



Expansion module connectable



Headset connectable



Self-labeling keys



Security (TLS & SRTP)

## Benefits

- High-resolution 3.5" graphical TFT display
- Dual-angle footstand: 46° and 28°
- Wall mountable
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port 1-Gigabit Ethernet switch (RJ45) IEEE 802.3
- Power over Ethernet IEEE 802.3af, Class 3
- USB headset<sup>(1)</sup> ready
- D7 Expansion Module<sup>(1)</sup> ready
- Support for USB WiFi stick
- Electronic Hook Switch (EHS)<sup>(1)</sup> support for wireless headsets
- Built-in Bluetooth compatibility

## Firmware

### Features

- 12 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX platforms

### Call Features

- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable)<sup>(2)</sup>
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold<sup>(2)</sup>
- Handling of up to 4 simultaneous calls
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup<sup>(2)</sup>
- Call park, call unpark<sup>(2)</sup>
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)<sup>(2)</sup>
- Unified Communications ready

### Audio

- Codecs:
  - G.711 A-law,  $\mu$ -law
  - G.722 (wideband)
  - G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort Noise Generator (CNG)
- Voice Activity Detection (VAD)

### Setup

- Configurable through web interface
- Provisioning:
  - Automatic loading of settings via HTTP/HTTPS/TFTP
  - DHCP Options 66/67
  - Snom Redirection Service
  - Remote management via TR-069 / TR-111

## Specifications

### Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

### User Interface

- Localization (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context-sensitive keys
- 16 programmable line / function keys with multicolor LEDs
- Paper inlay for labeling of function keys
- Dedicated keys for: Message, DND, Directory, Menu, Transfer, Hold
- Audio keys with LED indication: Mute, Speakerphone, Headset
- Volume key
- 4-way navigation key
- OK and Cancel keys
- Menu-driven user interface

### Security

- 802.1X authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server/client
- password-protected web interface
- VPN-support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

### Phone Features

- Dimensions (approx.):
  - 238 x 190 x 40 mm (LxWxD) w/o foot stand
  - 238 x 190 x 200/220 mm (LxWxD) with foot stand
- Weight (approx.): device 690g, footstand 230g
- Input voltage: 5Vdc (SELV)
- Power supply: PoE or 5Vdc power adapter<sup>(1)</sup>, 10 Watts
- Handset: 4P4C
- Headset: 4P4C; 4pin for snom EHS Advanced<sup>(1)</sup>
- Hearing-aid compatible (HAC) handset
- 1 x USB 2.0 host port, Type A, Hi/Full/Low-Speed
- Environmental conditions:
  - Ambient temperature: 0°C to 35°C (32°F to 95°F)
  - Storage temperature: -10°C to 45°C (14°F to 113°F)
  - Humidity: 5% to 95% (non-condensing)
- Included in delivery:
  - Phone unit
  - Footstand
  - Handset with cord
  - Ethernet cable
  - Quick Start Guide
- Color: black
- Part Number: 00003917 (all markets)

<sup>(1)</sup> Optional accessory (see below for part numbers)

<sup>(2)</sup> If supported by PBX

### Part numbers for optional accessories

- 00004011 D7 Expansion Module (black)
- 00004325 Power Adapter Snom A6 / EU clip
- 00004326 Power Adapter Snom A6 / US clip
- 00001168 UK clip for Snom A6
- 00001167 AUS clip for Snom A6
- 00004394 Snom Power Adaptor 10W
- 00004395 UK clip for Snom Power Adaptor
- 00002362 Snom EHS Advanced
- 00004341 A100M Headset
- 00004342 A100D Headset
- 00004405 A150 DECT Micro-Headset
- 00004387 A170 DECT-Headset
- 00004384 A210 USB WLAN Dongle
- 00004386 A230 USB DECT Dongle

### Type Approvals

- CE Mark
- FCC Class B
- Safety IEC 60950, CB

### Series Overview



On the internet

<https://www.snom.com/d765/>